

LSpcr® 1000



Spacer Fluid System / Cementing Additive for Maximum Plugging and Protection of the Wellbore During Cementing

Features and Benefits

- Near 100% return permeability
- Prevents cement fallback post placement
- Effective in high-temperature, highly permeable fractured and mechanically weak formations
- Protects the formation from damage by preventing invasion of filtrate and cement.
- Minimally invasive additive due to strong seal formation.
- Well bore strengthening
- Compatible in OBM, WBM and SBW
- 100% biodegradable and organic.
- Allows cement to return to the surface, preventing top-outs.
- Removes gelled fluids and enhances hole cleaning

Overview

LSpcr® 1000 has a proprietary particle size and shape distribution designed to form a minimally invasive seal that halts the invasion of filtrate and cement into the formation while promoting well bore stability and strength. With nearly 100% return permeability LSpcr® 1000 shield the cement from harm. LSpcr® 2000 should be added to the LSpcr® 1000 spacer system where large and mixed fractures are expected or total losses occur.

Applications

- Seals highly fractured and mechanically weak formations
- Seals depleted sands and micro-fractures
- Minimally invasive
- Protects, reinforces and strengthens the wellbore

Safety & Handling

For handling and safety information and instructions refer to the Product Safety Sheet by emailing Liquid Casing, Inc. at admin@liquidcasing.com. Refer to the safety data sheets (SDS) for handling, transport, environmental and first aid information by contacting admin@liquidcasing.com

Appearance	Typical temp. range	Typical concentration	Specific Gravity	Bulk Density	Absolute volume
<i>Tan granular, free flowing powder</i>	<i>Up to 400°F (204°C) BHST</i>	<i>10 to 25 lb/bbl (28.5 to 71.3 kg/m3)</i>	<i>1.5</i>	<i>33.09 lb/ft3 530 kg/m3</i>	<i>0.0799 gal/b (0.6671 L/kg)</i>

A product from *Liquid Casing, Inc. USA*